

Automatic Aniline Point Tester aap-6

- Ergonomically color-coordinated display for high visibility for everybody and intuitive switch operation.
- Enhanced versatility including Ethernet for LIMS, USB port for flash memory or keyboard, password protection and data storage (max.200 results).
- All-in-one chassis design: compact, light weight and premier exterior.

Intelligent Full-Auto operation

aap-6 automates the aniline point test of petroleum products. The theme of 6th generation is "Ergonomic, Versatile and Premium".

aap-6 is capable of covering a wide range of samples including transparent samples as well as dark / opaque samples.



User-friendly measuring cell

The measuring cell can be easily removed and placed on an analytical balance for weighing viscous samples, including solid samples, at ambient temperature. Optional water-jacketed measuring cells are also available for sub-ambient temperature.

Easy operation

Deliver the dried sample and aniline, enter the expected aniline point, and press the START key; the rest of the test procedures (such as heating, cooling and aniline point detection) are performed automatically. The operator has the option to report the result after either single determination or after multiple determinations.

Easier and safer aniline handling

For years, handling of the toxic aniline has been considered a hazardous operation. A bottle top dispenser can be connected to the measuring cell in order to directly deliver aniline without using a manual pipette operation. Upon completing a test, the operator discharges the aniline mixture from the bottom of the measuring cell, pours a cleaning agent, turns on the stirrer, and discharges the cleaning agent. The measuring cell can be cleaned without disassembling, making clean up both easier and safer.

Automatic Aniline Point Tester

aap-6

TANAKA

Specifications

Conforming standards	ISO 2977, ASTM D611, etc.		
Samples	Transparent or opaque/dark (<8.0 on ASTM color scale)		
Measuring range	Ambient +20 °C to 170 °C (338°F) For below ambient + 20 °C, use the optional water jacketed measuring cell and a cryostat.		
Temperature sensor	Pt100 in stainless steel sheath		
Aniline point detector	Photo-electric cell, with special detection circuitry		
Measuring cell	Modified u-tube type. vacuum jacketed glass cell with PTFE stopcock at the bottom for drainage.		
Display	5.7 inch color LCD with LED back light		
Heater	Immersion heater in stainless steel sheath : 20 W		
Sequence control	By an on-board microcomputer		
Test mode	Single, repeat (2 kinds, average is reported to nearest 0.05 °C), SPE and manual temp set		
I/O Port	Ethernet x 1 for LIMS USB x 1 for Flash Memory or Keyboard RS-232C x 1 for PC or Optional Printer		
Safety mechanism	Automatically shuts off and the problem is reported by buzzer and display, in case: (a) EAP+10 °C or at 170 °C is reached, (b) Temperature sensor is found defective, (c) Light projector or receiver is found defective, (d) Built in battery is found drained out or, (e) Control computer disappears (no display)		
Size (W x D x H)	230 mm x 470 mm x 490 mm (23 cm x 47 cm x 49 cm / 9 in x 18.5 in x 19.2 in)		
Weight	14 kg / 30.8 lb		
Installation site	10 °C to 40 °C RH : Less than 90%		
Power supply	AC 100 to 240 V 50 / 60 Hz 125 W (max.)		
Ordering information	Code No.	Part Name	Qty
Standart accessories	1. AAP-03-011	Measuring cell, upper,2-inlet	1pc
	2. 010-00-224	Measuring cell, lower	1pc
	3. MPC-02-032	AC power cord 100 / 120 V 3.0 m	or
	4. MPC-02-033	AC power cord 220 / 240 V 2.5 m	
	5. AAP-02-423	Measuring cell stand	1pc
	6. 520-00-201	Hex driver	1pc
	7. 320-00-021	Fuse ET2A	1pc
	8.	Instruction manual	1pc
Optional accessories	Code No.	Part Name	Qty
	1. 010-00-225	Water jacketed measuring cell, lower	1pc
	2. 070-00-068	Printer B52-80TS with connecting cable	1pc
	3. 070-00-093	Printer roll paper (2rolls / pack)	1pc
	4. 070-00-281	Mini USB keyboard	1pc
	5. 010-00-223	Measuring cell, upper,1-inlet	1pc
	6. AAP-02-031	Insulating tube	1pc
Suggested spares	Code No.	Part Name	Qty
	1. AAP-03-011	Measuring cell,upper, 2-inlet	1pc
	2. 010-00-224	Measuring cell, lower	1pc
	3. AAP-04-411	Temperature sensor	1pc
	4. AAP-04-011	Heater	1pc
	5. 320-00-021	Fuse ET2A	1pc



PTFE tubing connected to measuring cell for direct delivery from bottle-top dispenser for a safer aniline handling. PTFE tubing and fitting are **an option** and not provided with aap-6.

Specifications subject to change without prior notice.

201411P

2139 High Tech Rd. | State College PA 16803 | USA
800-676-6232 | 814-343-8000 | Fax: 814-353-8007
sales@cannoninstrument.com | cannoninstrument.com

Tanaka Scientific Limited
CANNON
INSTRUMENT COMPANY